

| Datasheet<br>2250kVA,3Phase,60 Hz,ONAN, 13200 D - 480 Y /277<br>Pad Mounted Transformer |                                               |           | <br>OMEX - For the Ones Powering America |
|-----------------------------------------------------------------------------------------|-----------------------------------------------|-----------|----------------------------------------------------------------------------------------------------------------------------|
| S.No.                                                                                   | Particulars                                   | U.O.M     | Description                                                                                                                |
| 1                                                                                       | Rated KVA                                     | kVA       | 2250                                                                                                                       |
| 2                                                                                       | No. of Phases                                 | No.       | 3                                                                                                                          |
| 3                                                                                       | Primary Voltage                               | Volts     | 13200 D                                                                                                                    |
| 4                                                                                       | Secondary Voltage                             | Volts     | 480 Y /277                                                                                                                 |
| 5                                                                                       | Vector Group                                  | Symbol    | Dyn1                                                                                                                       |
| 6                                                                                       | Service                                       |           | Outdoor, Pad Mounted                                                                                                       |
| 7                                                                                       | Standard                                      |           | IEEE C57.12.34, IEEE C57.12.00, IEEE C57.12.90                                                                             |
| 8                                                                                       | Fluid Type                                    |           | Type II Mineral Oil                                                                                                        |
| 9                                                                                       | Type of cooling                               |           | ONAN                                                                                                                       |
| 10                                                                                      | Percentage Impedance                          | %         | 5.75% (+/- 7.5% IEEE Tol.)                                                                                                 |
| 11                                                                                      | Winding Temperature Rise                      | °C        | 65 °C                                                                                                                      |
| 12                                                                                      | Frequency                                     | Hz        | 60 Hz                                                                                                                      |
| 13                                                                                      | Taps                                          | %         | +5% to -5% in steps of 2.5%                                                                                                |
| 14                                                                                      | Winding Material (Primary/Secondary)          |           | AL/AL                                                                                                                      |
| 15                                                                                      | BIL Rating                                    | kVp/KVrms | HV:LI 95, AC 34; LV: LI 30 AC 10                                                                                           |
| 16                                                                                      | Color                                         |           | Munsell Green 7GY3.29/1.5                                                                                                  |
| 17                                                                                      | Tank Material                                 |           | Mild Steel                                                                                                                 |
| 18                                                                                      | UL Listed                                     |           | Yes                                                                                                                        |
| 19                                                                                      | Efficiency: DOE-2016 for rating ≤2500kVA @UPF | %         | 99.51                                                                                                                      |
| 20                                                                                      | HV Termination                                |           | Dead Front Loop Feed                                                                                                       |
| 21                                                                                      | LV Termination                                |           | Live Front Radial Feed                                                                                                     |
| 22                                                                                      | Switch Options                                |           | 4 Position LBOR Switch (T-blade)                                                                                           |
| 23                                                                                      | Standard Accessories                          |           | 15KV, 600Amps Bushing Wells, BIL-95kV                                                                                      |
|                                                                                         |                                               |           | 1.2kV, 3000Amps Epoxy Bushing ( Spade Type terminal, 6 holes)                                                              |
|                                                                                         |                                               |           | De-energised Off Circuit Tap Changer                                                                                       |
|                                                                                         |                                               |           | Pressure Relieve Valve                                                                                                     |
|                                                                                         |                                               |           | Pressure and Vacuum gauge without contact                                                                                  |
|                                                                                         |                                               |           | Lifting Lugs                                                                                                               |
|                                                                                         |                                               |           | Oil level guage without contact                                                                                            |
|                                                                                         |                                               |           | Drain Valve with Sampler                                                                                                   |
|                                                                                         |                                               |           | Nitrogen/dry air Blanket                                                                                                   |
|                                                                                         |                                               |           | Dial Type oil temperature indicator with maximum reading pointer                                                           |
|                                                                                         |                                               |           | Radiator-detachable                                                                                                        |
|                                                                                         |                                               |           | Schrader Valve                                                                                                             |
|                                                                                         |                                               |           | Bay-o-net fuse with Backup CLF                                                                                             |
| 24                                                                                      | Other Accessories                             |           | Seismic Anchoring provisions                                                                                               |
|                                                                                         |                                               |           | Based on requirements, accessories with contacts                                                                           |
| OMEX PRODUCT CODE:2250kVA-13200D480Y-3PH-ONAN-MS-PM-L                                   |                                               |           |                                                                                                                            |